

Stop/Tail, Turn, Warning, Backup, and Backup with Warning

**Certified for ambulance  
and EMS vehicle use.**

**Heavy-duty bezel optional;  
sold separately.**



**Warning**



**Backup**



**Stop/Tail and Turn**

### Mounting Options



**Stud Mount**



**Quick Mount**



**Screw Mount**

### Features

- Powerful lighting output at 180 degree viewing angles perfect for fire and EMS apparatuses
- Extremely functional and customizable for use as stop/tail, turn, backup, backup with warning, scene or warning light
- Rugged weather-resistant IP67 enclosure
- Five-wire nano connector with 18 inch flying leads
- Durable clear silicone lens
- Industry standard bolt pattern location
- Sync 2 compatible, with other Sync 2 products (warning and backup with warning lights only)
- bluePRINT® compatible, runs in slave mode

AVAILABLE COLORS	All standard single, dual or tricolors, split warning, red stop/tail, amber turn or white backup
INPUT VOLTAGE RANGE	9-32 Vdc
FLASH PATTERNS	14, warning, stop/tail, turn, backup, and backup with warning
DIMENSIONS	Length 6.37" (16.17 cm) Height 4" (10.16 cm) Depth 1.01" (2.56 cm)
CERTIFICATIONS	SAE J595 Class 1 certified; CA Title 13 certified; NFPA, KKK-1822-F and FMVSS-108 (backup, stop/tail and turn)
MOUNTING	Stud, quick or screw mounts
WARRANTY	Five-year warranty