

UNIVERSAL UNDERCOVER™ LED INSERT with WATER PROOF CONNECTOR

WALUC2ØØ1(x)-WP

EACH INSERT INCLUDES: 1 - ELUC2SØ1Ø(x) LED INSERT WITH 18" HARNESS AND WEATHER PACK CONNECTOR



WEATHER PACK CONNECTOR



Please see Instruction Sheet for ELUC2S010(x) for Technical Specifications and Illustrations

Important Information: -

• DO NOT cut the wires between in-line flasher and light head

• Warning devices are strictly regulated and governed by Federal, State and Municipal ordinances. These devices shall be used ONLY on approved vehicles. It is the sole responsibility of the user of these devices to ensure compliance.

• DO NOT install this product or route any wires in the Air Bag Deployment Zone. Refer to your vehicle Owner's Manual for the location of any air bag deployment zones.

• DO NOT connect this device to a strobe power supply. This product is self-contained and does not require an external strobe power supply.

SoundOff Jignal IIII.

To review our Limited Warranty Statement & Return Policy for this or any SoundOff Signal product please visit our website at www.soundoffsignal.com and select the "Warranty & Returns" link along the left column of our home page. If you have questions regarding this product please contact Technical Services, Monday - Friday, 8 am to 5 pm at 1.800.338.7337, press #4 to skip the automated message. Questions or comments that do not require immediate attention may be emailed to techsupport@soundoffsignal.com.

1.800.338.7337. / www.soundoffsignal.com / Thank you for trusting us with your safety!

INSTALLATION INSTRUCTIONS

Your WALUC2ØØ1(x)-WP is identical to the ELUC2SØ1Ø(x) UNIVERSAL UNDERCOVER[™] LED INSERT with the exception of the connecting cable (shown at left). The cable is 18" long and exits from the flasher (not shown) and the lack of the GREEN wire which would normally be used for CRUISE mode. The GREEN wire is sealed inside the cable and may be used at some future date if desired.

Follow the instructions for the installation of the ELUC2SØ1 $\emptyset(x)$.

The female Weather Pack connector (customer supplied) is installed in the male connector shown with the wire color assignments shown below. Make certain that wire colors are mated and that connector is fully engaged.

WIRE CONNECTIONS (for WALUC2Ø1Ø(x)-WP <u>ONLY</u>)

WIRE HOOK-UP TABLE	
WIRE COLOR:	CONNECT TO:
RED	+10-16Vdc
BLACK	Ground (-)
WHITE	Pattern Select/Sync



This product must be mounted with sufficient clearance from any plastic parts. Failure to do so may result in permanent damage to the housing.

