


STROBE PREP PACKAGE



- HIGH CURRENT interconnects must be properly terminated. Poor crimp quality can cause heat build-up and fire. Follow crimp connector manufacturer instructions.
- D0 NOT install this product or route any wires in the Air Bag Deployment Zone. Refer to vehicle Owner's Manual for deployment zones.
- Unit may become hot to touch during normal operation.
- Failure to properly install connectors, fuses or wiring may cause vehicle failure or fire.
- Installation must only be performed by trained technician. Installer must determine vehicle wiring configuration and proper integration of system.
- Use proper wire gauge. All power wires connecting to positive (+) or negative (-) battery terminal or local chassis ground (-) must be sized to supply at least 125% of max. current and properly fused at power source.
- Install protective grommets when routing wire through firewall or metal.

STROBE TUBE CONNECTION:

Installer is responsible for selection of a strobe supply to drive the strobe tube. The strobe power supply should be capable of a 20 watt output. Follow all manufacturer's directions pertaining to the strobe power supply when installing for proper operation. Observe any requirements for installation safety and proper fusing of the power supply. Observe safe installation and operation by ensuring protection of the power cable which includes no cuts, abrasions or wear areas left unprotected.

The out put of the strobe power supply must be connected to the 3-wire gray cable from the lightbar. Connect the red wire of the strobe tube to the positive wire of the strobe power supply and connect the black wire (trigger/parking brake override) of the strobe tube cable to the appropriate control wire from the strobe power supply.

The strobe tube is warranted for a period of one year.



NOTICE:



Installers and users must comply with all applicable federal, state and local laws regarding use and installation of warning devices.

Improper use or installation may void warranty coverage. To review our Limited Warranty Statement & Return Policy for this or any SoundOff Signal product, visit our website at www.soundoffsignal.com/sales-support. If you have questions regarding this product, contact Technical Services, Monday - Friday, 8 a.m. to 5 p.m. at 1.800338.7337 (press #4 to skip the automated message). Questions or comments that do not require immediate attention may be emailed to techservices@soundoffsignal.com.

1.800.338.7337 / www.soundoffsignal.com

SUPERIOR CUSTOMER RELATIONSHIPS. SMARTLY DESIGNED LIGHTING & ELECTRONIC SOLUTIONS.