

## mpower® Traffic Controller



Order today for shipments beginning April 1.

### Features

- Designed for interior or exterior use
- Designed with six inch modules
- Available in lengths of four, six, eight or ten modules
- Eight module is available in split or full; eight in a row or two different assemblies of four modules connected with harness
- Wire harness lengths available in 3, 15 or 25 feet



### Specs

**INPUT VOLTAGE RANGE** 9-32 Vdc

**NUMBER OF LEDs AND MAXIMUM CURRENT DRAW @ 12.8 Vdc**  
 0.36 Amp (flashing red)  
 0.62 Amp (peak red)  
 0.60 (flashing amber, blue, green or white)  
 0.90 Amp (peak amber, blue, green or white)

**NUMBER OF LEDs and MAXIMUM WATTAGE @ 12.8 Vdc**  
 4.6 Watt (red)  
 7.7 Watt (amber, blue, green or white)

**LED COUNTS** Single color: 6 LEDs Dual color: 12 LEDs Tricolor: 18 LEDs

**FLASH PATTERNS**  
**Warning** 28 single, 22 dual and 19 tricolor  
**Arrow** 11

**OPERATING TEMPERATURE** -40° C to + 65° C / -40° F to +150° F

#### DIMENSIONS

**Lengths**  
 4 Module: 26" (66 cm)  
 6 Module: 38.75" (98 cm)  
 8 Module: 52" (133 cm)  
 10 Module: 64.25" (163 cm)

**Height** 1.6" (3.9 cm)  
**Depth** 2.4" (6.2 cm)

**CERTIFICATION**  
 SAE J845 Class 1 certified  
 SAE J595 Class 1 certified  
 CA Title 13, Article 22 compliant  
 IP67

**WARRANTY** Five-year

Contact your sales representative for further details.

PO Box 206 / 3900 Central Parkway  
 Hudsonville, MI 49426

800.338.7337 / 616.896.7100  
 Fax 616.896.1226 / Order fax 616.896.1286