

nLINE Surface Mount Light

New-and-improved model features a bracket mount for use on any vehicle.



48 Inch Length Shown



48 Inches
60 Inches
72 Inches

ENL148(x)
ENL160(x)
ENL172(x)

Replace (x) in the Order Number for Standard Color Selection

Solid Colors A = ● B = ● R = ●

Split Colors D = ●○ E = ●○ F = ●○ J = ●●

Features

- New and improved bracket mount with adjustable bracketry (straight and 60 degrees) included
- Prime applications include rocker panels, push bumpers, tailgates and headache racks
- Distributes exceptional profile visibility to dangerous intersections
- Compact extruded aluminum housing is visually inconspicuous and weather resistant
- 19 inches of wire cable for hard wire installation

Technical Specifications

INPUT VOLTAGE	10-16 Vdc
CURRENT DRAW	0.58 Amp @ 12.8 vdc
LIGHT SYNC	6 single nLINE lighthead
FLASH PATTERNS	10 flash patterns
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	
Widths	48" (121.9 cm); 60" (152.4 cm) or 72" (182.9 cm)
Height	2.25" (5.7 cm) (all lights)
Depth	.75" (1.9 cm) (all lights)
MOUNTING	Bracket mount

Contact your sales representative for further details.