

Pinnacle Mini Lightbar

Optimal lighting output spread far and wide, in a compact footprint



Permanent Mount









Magnetic Mount

FEATURES

- Multiple mounting and LED color options to meet your needs
- High optical performance at a great price
- Low profile at only 2.93" high
- 12 ft cord w/ 12v cigar plug
- Non-volatile memory – recalls last flash pattern used
- Magnetic mount includes a rocker switch panel
- 7300 dual color model has independent color control

SPECIFICATIONS

	Pinnacle 7000	Pinnacle 7300	NEW
Standard Part Number*	EPL7*	EPL73*	
Voltage	10-16 Vdc	10-30 Vdc	
Current Draw	2 Amps @ 12.8 Vdc	2 Amps @ 12.8 Vdc	
Operating Temperature	-40° C to +65° C (-40° F to +149° F)	-40° C to +65° C (-40° F to +149° F)	
Flash Patterns	28+	17	
Light Sync	Not available	Sync2 - up to 24 devices <i>(permanent mount only)</i>	
LED Count	24	Single - 24, Dual - 48	
LED Color Capabilities	Single, split	Single, dual, split	
Single LED Colors			
Dual LED Colors	Not available		
Split LED Colors		Programming w/ dual color	
Lens Colors		 <i>(amber LEDs only with amber lens)</i>	
Dimensions	14.16" L x 2.93" H x 8.27" D	14.16" L x 2.93" H x 8.27" D	
Mounts	Magnetic mount, permanent mount	Magnetic mount, permanent mount	
Certifications**	SAE J845	SAE J845, CA Title 13, CISPR25	



**Scan to order
or learn more**



CONTACT

Toll free 800.338.7337
Direct 616.896.7100
soundoffsignal.com

PO Box 206
Hudsonville, MI 49426
customerservice@soundoffsignal.com

* Standard part numbers can be found on soundoffsignal.com

**** Complete certification lists can be found on installation sheet**